

VMC 8030_{B-II}

CNC VERTICAL MACHINING CENTER with FADAL 64MP CNC CONTROLLER

Specifications

TRAVEL	
X-axis Travel (in.)	80
Y-axis Travel (in.)	32
Z-axis Travel (in.)	30
Spindle nose to table (in.)	5-35
Spindle center to column (in.)	34.375
TABLE	
Table Dimensions (in.)	88 x 30
T-Slot Dimensions (in.)	(5) 5.5 x .709 x 1.25
Max. Table Load (lbs.)	4,800
SPINDLE	
Spindle Type	Cat-40
Spindle Speed (RPM)	10,000
Spindle Torque (ft. lbs.)	225
Spindle Motor (HP) Peak	22.5
FEED	
Rapid Traverse Rate X,Y & Z (IPM)	787 / 787 / 590
Ballscrew Diameter X,Y & Z Axis (mm)	50
ATC	
Tool Capacity	24
Tool Change Type	Dual Arm
Max. Tool Weight (lbs.)	15
Max. Tool Diameter (in.) (with adjacent tool)	4.9 (3.1)
Max. Tool Length (in.)	11.8
Tool Selection Method	Random
OTHER	
Machine Dimensions L x D x H (in.)	216 x 138 x 132
with Chip Conveyor	272 x 138 x 132
Machine Weight (lbs.)	33,000
Considerations subject to about a without paties	•

Specifications subject to change without notice

STANDARD FEATURES

Box Way Construction Spindle Oil Cooler 3 LED Work Lamps (2 Bar/1 Round) **Fully Enclosed** Spindle Air Blast **Automatic PDI Lubrication System Operation Indication Lamp Rigid Tapping Chip Flush System** 3-Way Chip Augers High Torque (22.5hp peak) Remote MPG







OPTIONAL FEATURES

Chip Conveyor BT40 4th Axis Ready 5th Axis Ready **RTCP**

FR-8, FR-15 Rotary Table FTR-8 Tilting Table 30 position and 40 position **DATC**

OPTIONAL PROBING

Tool Pre-Setter (wired) Tool Pre-Setter (wireless) X, Y, Z Coordinate (wireless)

FADAL 64MP CONTROLLER

Backward Compatible 88HS & MP Memory 256mb 2000 Blocks/sec Look Ahead **Networking & USB Ports High Speed Machining**





Authorized Fadal Dealer



www.Fadal.com 844.323.2526