

....

VMC 2015

CNC Vertical Machining Center with Fadal 64MP CNC Controller

2 YEAR WARRANTY 2-Year/4,000 User-Hours

▶ 844.323.2526
 ▶ SALES@FADAL.COM



VMC 2015

-adol



VMC 2015

STANDARD FEATURES


Dual Supported Auto Lubricated

2- Year /4,000 User-Hours

Ball Screws

Warranty

- Spindle Oil Cooler
- LED Work Lamp
- Fully Enclosed
- Spindle Air Blast
- Automatic PDI Lubrication
 System
- Operation Indication Lamp
- Rigid Tapping
- Chip Wash Down System
- Linear Roller Bearing Ways



SPECIFICATIONS

TRAVEL	
X-Axis Travel (in.)	19.7″
Y-Axis Travel (in.)	15.7″
Z-Axis Travel(in.)	16
Spindle nose to table (in.)	5.9-21.6
Spindle center to column (in.)	16.9
TABLE	
Table Dimensions (in.)	25.6 x 15
T-Slot Dimensions (In.)	(3) 3.94 x .709
Max. Table Load (lbs.)	440
SPINDLE	
Spindle Type	BT-30
Spindle Speed (RPM)	12,000/15,000*/20,000*
Spindle Torque (ft. lbs)	43.5
Spindle Motor (HP) Peak	10/7.5*
FEED	
Rapid Travel Rate X,Y & Z (IPM)	1,890
Ballscrew Diameter X, Y & Z Axis (mm)	32
ATC	
Tool Capacity	20
Tool Change Type	Dual Arm
Tool Change Time (sec.)	1.0 Tool to tool
Max. Tool Weight (Ibs.)	6.6
Max. Tool Diameter (in.) (with adjacent tool)	4(2.4)
Max. Tool Length (In.)	7.9
Tool Selection Method	Random
OTHER	
Machine Dimensions L x W x H (in.)	64 x 94 x 94
Machine Weight (lbs.)	6,160

Specifications subject to change without notice

* Optional

OPTIONAL FEATURES

- Remote Manual Pulse Generator (RMPG)
- 4th Axis Prewire
- 4th Axis Servo Disconnect
- 5C Collet Closure Pneumatic
- FR-6D Standard Rotary Table (Req. 4th Axis disconnect)
- FR-6A High Speed Rotary Table (Req. 4th Axis disconnect)
- FR-6D Tailstock (Manual Clamp w/Quill)

- 6 Inch 3-Jaw Chuck with Flange
- 15K RPM Spindle
- 20K RPM Spindle
- 24K RPM Motorized Spindle
- Hard Wired Tool Preseter
- Wireless Tool Presetter
- Wireless Touch Probe

FADAL 64MP CONTROLLER

- Backward Compatible 88HS & MP
- Memory 4GB
- 3,000 Blocks/sec Look Ahead
- Networking & USB Ports
- High Speed Machining



Fadal.com

MADE FOR MACHINISTS, BY MACHINISTS.